

LPC-HG system Hygienic Range

NEW

- IP66
- IP67
- IP68
2 bar
- IP69



Conduit


LPC-WFG	LPC-BUFG	LPC-GFG
<p>Construction: Smooth bore, smooth cover, helically formed PVC, flexible conduit with spiral uPVC reinforcement and flexible PVC jacket.</p> <p>Colour: White.</p> <p>Typical Applications: Suitable for repeat contact with all food types, excluding fatty foods, at full temperature.</p> <p>The flexible PVC is manufactured from FDA approved ingredients and has been independently tested to European Food regulation 10/2011.</p>	<p>Construction: Smooth bore, smooth cover, helically formed PVC, flexible conduit with spiral uPVC reinforcement and flexible PVC jacket.</p> <p>Colour: Blue.</p> <p>Typical Applications: Suitable for repeat contact with all food types, excluding fatty foods, at full temperature.</p> <p>The flexible PVC is manufactured from FDA approved ingredients and has been independently tested to European Food regulation 10/2011.</p>	<p>Construction: Smooth bore, smooth cover, helically formed PVC, flexible conduit with spiral uPVC reinforcement and flexible PVC jacket.</p> <p>Colour: Grey.</p> <p>Typical Applications: Suitable for repeat contact with all food types, excluding fatty foods, at full temperature.</p> <p>The flexible PVC is manufactured from FDA approved ingredients and has been independently tested to European Food regulation 10/2011.</p>

Fittings

FCC-SS

stainless steel (316L) P clips

P clip to support conduit.



Multiflex Consulting Aps

Tel: 5332 7083

nominal size (mm)	LPC-WFG					LPC-BUFG					LPC-GFG					part number
	part number	reel length (m)	outside dia (mm)	inside dia (mm)	min inside bend radius (mm)	part number	reel length (m)	outside dia (mm)	inside dia (mm)	min inside bend radius (mm)	part number	reel length (m)	outside dia (mm)	inside dia (mm)	min inside bend radius (mm)	
12	LPCWFG16	30	17.8	12.6	50	LPCBUFG16	30	17.8	12.6	50	LPCGFG16	30	17.8	12.6	50	FCC16-SS
16	LPCWFG20	10, 30	21.1	16.0	70	LPCBUFG20	10, 30	21.1	16.0	70	LPCGFG20	10, 30	21.1	16.0	70	FCC16-SS
20	LPCWFG25	10, 30	26.4	21.0	90	LPCBUFG25	10, 30	26.4	21.0	90	LPCGFG25	10, 30	26.4	21.0	90	FCC20-SS
25	LPCWFG32	10, 30	33.1	26.5	140	LPCBUFG32	10, 30	33.1	26.5	140	LPCGFG32	10, 30	33.1	26.5	140	FCC25-SS
32	LPCWFG40	10, 30	41.8	35.4	190	LPCBUFG40	10, 30	41.8	35.4	190	LPCGFG40	10, 30	41.8	35.4	190	FCC32-SS
40	LPCWFG50	10, 30	47.9	40.0	240	LPCBUFG50	10, 30	47.9	40.0	240	LPCGFG50	10, 30	47.9	40.0	240	FCC40-SS
50	LPCWFG63	10, 30	59.7	51.3	270	LPCBUFG63	10, 30	59.7	51.3	270	LPCGFG63	10, 30	59.7	51.3	270	FCC50-SS
63																FCC63-SS*

Ordering Notes

- * Indicates parts made to order on request and may be subject to MOQ and lead time
- Available on request:
 - additional sizes
 - alternative threads

Accessories



see page 126