





Non-metallic systems are typically lighter, easier to work with and more cost effective to install.

With advances in material technologies non-metallic systems can provide an alternative solution

where typically only metal systems had been considered previously.

Multiflex Consulting Aps  
Tf.: 5332 7083

# Non-Metallic Conduit and Fittings

FPAS	FPAL	FPAH	FPASC
 <p><b>Construction:</b> Standard weight, flame retardant nylon (PA6) corrugated flexible conduit. <b>Colour:</b> Black or Grey (RAL 7031). Orange available on request.* <b>Typical Applications:</b> All types of machinery, public buildings.</p> <ul style="list-style-type: none"> <li>Highly flexible and high fatigue life</li> <li>High impact strength and recovers if crushed</li> <li>Temperature range -40°C to +120°C (-20°C to +100°C for moving applications)</li> <li>Lloyd's Register Type Approval</li> <li>UL recognised</li> <li>Low Fire Hazard (LFH), see page 149</li> <li>UL 94 V2 flame retardancy</li> <li>Halogen, sulphur and phosphorus free</li> <li>UV resistant (black)</li> <li>Abrasion resistant</li> <li>Highly resistant to solvents and oils</li> <li>Slit version also available FPAS-S please contact us</li> </ul>	 <p><b>Construction:</b> Light weight nylon (PA6) corrugated flexible conduit. <b>Colour:</b> Black or Grey (RAL 7031). <b>Typical Applications:</b> Machines where lower mechanical protection is required and buildings.</p> <ul style="list-style-type: none"> <li>Highly flexible and high fatigue life</li> <li>High impact strength and recovers if crushed</li> <li>Temperature range -40°C to +120°C (-20°C to +100°C for moving applications)</li> <li>UL recognised</li> <li>Highly resistant to solvents and oils</li> <li>Self extinguishing</li> <li>Halogen, sulphur and phosphorus free</li> </ul>	 <p><b>Construction:</b> Heavy weight, flame retardant, nylon (PA6) corrugated flexible conduit. <b>Colour:</b> Black. <b>Typical Applications:</b> All types of machinery and public buildings where high mechanical strength required.</p> <ul style="list-style-type: none"> <li>High mechanical strength</li> <li>High impact resistance</li> <li>Temperature range -40°C to +120°C (-20°C to +100°C for moving applications)</li> <li>UL recognised</li> <li>Low Fire Hazard (LFH), see page 149</li> <li>UL 94 V2 flame retardancy</li> <li>Halogen, sulphur and phosphorus free</li> <li>UV resistant</li> <li>Abrasion resistant</li> <li>Highly resistant to solvents and oils</li> </ul>	 <p><b>Construction:</b> Standard weight, flame retardant nylon (PA6) corrugated flexible conduit. <b>Colour:</b> Black or Grey (RAL 7031). <b>Typical Applications:</b> All types of machinery, public buildings where UL listed is a requirement.</p> <ul style="list-style-type: none"> <li>Highly flexible and high fatigue life</li> <li>High impact strength and recovers if crushed</li> <li>Temperature range -40°C to +120°C (-20°C to +100°C for moving applications)</li> <li>UL listed</li> <li>Lloyd's Register Type Approval</li> <li>Low Fire Hazard (LFH), see page 149</li> <li>UL 94 V2 flame retardancy</li> <li>Halogen, sulphur and phosphorus free</li> <li>UV resistant (black)</li> <li>Abrasion resistant</li> <li>Highly resistant to solvents and oils</li> </ul>

european (NW) sizes	nominal size (mm)	pitch	FPAS				FPAL				FPAH				FPASC								
			part number	reel length (m)	outside dia (mm)	inside dia (mm)	min inside bend radius (mm)	part number	reel length (m)	outside dia (mm)	inside dia (mm)	min inside bend radius (mm)	part number	reel length (m)	outside dia (mm)	inside dia (mm)	min inside bend radius (mm)	part number	reel length (m)	outside dia (mm)	inside dia (mm)	min inside bend radius (mm)	
7	10	F	FPAS10	50	10.0	6.3	15	FPAL10	50	10.0	6.5	15											
8	11	F	FPAS11	50	11.5	8.2	20	FPAL11	50	11.5	8.4	20											
10	13	F	FPAS13	25, 50	13.0	9.8	25	FPAL13	50	13.0	10.0	25	FPAH13	50	13.0	9.0	35						
12	16	F	FPAS16	25, 50	15.8	11.8	35	FPAL16	50	15.8	12.0	35	FPAH16	50	15.8	11.5	45						
14	18	F	FPAS18	50	18.5	14.2	40	FPAL18	50	18.5	14.2	35											
	20	C	FPAS20	10, 25, 50	20.0	14.8	45	FPAL20	50	20.0	15.0	40											
17	21	F	FPAS21	10, 25, 50	21.2	16.7	45	FPAL21	50	21.2	16.9	40											
	21	C											FPAH21	50	21.2	15.5	55	FPAS21C	50	21.2	16.0	45	
	25	C	FPAS25	10, 25, 50	25.0	19.1	50	FPAL25	50	25.0	19.3	45											
23	28	F	FPAS28	10, 25, 50	28.5	22.8	50	FPAL28	50	28.5	23.0	45											
23	28	C																					
29	34	C	FPAS34	25, 50	34.5	28.1	60	FPAL34	25, 50	34.5	28.3	55											
29	34	F	FPAS34F*	50	34.5	28.8	60						FPAH28	50	28.5	21.3	60	FPAS28C	50	28.5	21.7	50	
36	42	C	FPAS42	10, 25, 50	42.5	35.5	70	FPAL42	25	42.5	35.7	65	FPAH42	25	42.5	34.6	80	FPAS42C	25	42.5	35.5	70	
48	54	C	FPAS54	10, 25, 50	54.5	47.2	80	FPAL54	25	54.5	47.4	80	FPAH54	25	54.5	46.0	90	FPAS54C	25	54.5	47.2	80	
56	67	C	FPAS67	10	67.2	56.3	130	FPAL67	10	67.2	56.5	110						FPAS67C	10	67.2	56.3	130	

For larger diameter conduit see page 74

## Ordering Notes

- Specify Black or Grey (B = Black, G = Grey) and reel length eg: FPAS21B-50M for a Black 50m reel
- Some reel lengths are MTO in grey
- See cutting tool page 131
- \* Indicates parts made to order on request and may be subject to MOQ and lead time
- Available on request:**
  - longer lengths and bulk packaging
  - cut lengths and assemblies
  - other colours
  - full copies of independent test results confirming LFH properties
- conduit with pre-installed draw wire
- fine pitch 34mm sizes
- Contractor Packs available see page 132 & 133
- For LFH performance see page 149