

Tools

The following tools and accessories are available to aid installation. See page 140 for cutting and assembly advice. Alternatively visit our website & view our handy video clips to aid your installation.

clamp

cutting vice to hold metallic conduits and guide hacksaw (16-50mm).



Part Number

BSB clamp

hacksaw blade

fine tooth (32 TPI) blade for standard hacksaw.



Part Number

HACKSAWBLADE

bandsaw

bench mounted, 240v, fine toothed (32TPI) bandsaw.



Part Number

BANDSAW
BANDSAWBLADE (spare blades)

conduit cutter

for any non metallic flexible and rigid conduits.



Part Number

CC01 up to 34mm conduits
CC02 up to 67mm conduits

slitting tool

can be used to slit all corrugated conduits down to 13mm.



Part Number

CS01 slitting tool

slit conduit insertion tool

for easy installation of wires into slit conduit.



Part Number

for conduit

ST16 **FPYS16 + FPYS12**
ST20 **FPYS20**
ST25 **FPYS25**
ST32 **FPYS32**

removal tool for push in Flexilok® fittings (see page 68)



Part Number

For use with:

RTPF20 **FLK16-PL20, FLK20-PL20, FLK21-PL20**
RTPF25 **FLK25-PL25, FLK28-PL25**
RTPF32 **FLK34-PL32**

4 tooth Flexilok® Removal tool for use with 42mm & 54mm sizes (see page 68)



Part Number

For use with:

FLK42RT **FLK42-M40, FLK42-M50, FLK42-PG36**
FLK54RT **FLK54-M50, FLK54-M63, FLK54-PG48**